

OFFICE OF NAVAL RESEARCH

Contract No. NOO014-77-C-0685

Task No. NR 053-669

TECHNICAL REPORT No. 3

Low Temperature Fluorination of Aerosol and Condensed Phase Sol Suspensions of Hydrocarbons Utilizing Elemental Fluorine



bу

James L. Adcock, Kiyoshi Horita and Ehrengard B. Renk
Department of Chemistry
University of Tennessee at Knoxville
Knoxville, Tennessee 37916

Prepared for submission

to

Journal of American Chemical Society

Reproduction in whole or in part is permitted for any purpose of the United States Government

Approved for public release; distribution unlimited

DE FILE COPY

80 11 10 126

20. APENIACT (Continue on reverse side if necessary and identify by block number)

This report outlines the development of a new concept in low temperature direct fluorination. This method involves the reaction of gaseous elemental fluorine upon a solid-phase particulate aerosol at temperatures below room temperature. The rationale for the development of this method is that is a flow process but preserves the low temperature, solid phase fluorination features of the low temperature gradient reactor system developed by Adcock, Marashin and Lagow while eliminating the inherent

DD 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (Then Date Briefs 346670 LAN

S/N 0102- LF- 014- 6601

reliance on low temperature mass transport which results in long reaction times and the essentially batch nature of gradient reactor process.

This report discusses the development of a reliable aerosol fluorinator capable of achieving high yields of perfluorinated hydrocarbons via a photochemical fluorination stage. The aerosol system also produces partially fluorinated species in a controlled manner in high yields. Data presented suggests that fluorine reacts preferentially with methyl group hydrogens in the order CH₃>CH₂F>CHF₂. Data also shows that HF produced in the reactor does not solvolyse acid sensitive groups.

S/N 0102- LF- 014- 6601

LOW TEMPERATURE FLUORINATION OF AEROSOL

SUSPENSIONS OF HYDROCARBONS

UTILIZING ELEMENTAL FLUORINE

by

James L. Adcock and
Ehrengard B. Renk
Department of Chemistry
University of Tennessee
Knoxville, Tennessee 37916

Abstract

This work describes a new concept in direct fluorination methodology and an apparatus designed to achieve conditions necessary for the rapid, continuous partial or complete fluorination of hydrocarbon molecules under controlled conditions of temperature and concentration. Results from the fluorination of neopentane are presented which indicate that although the degree of fluorination for a given set of conditions indicates a gaussian distribution, investigation of specific isomers indicate significant deviations from statistical isomer distributions in fluorinated neopentanes. Photochemical assisted fluorinations of neopentane, 1,4-dioxane, cyclohexane and 2,2-dimethyl-1,3-dioxolane are described which produce the perfluorinated analogs directly in good purity and in high yields.

4000	ssion For	
DEIC DEIC Ureni	GTARI	0.0
By Distr	ibution/	
	lability C	
Dist	Avail and, Special	/or

The Low Temperature Fluorination of Aerosol
and Condensed Phase Sol Suspensions of Hydrocarbons
Utilizing Elemental Fluorine

Introduction

The fluorination of hydrocarbon molecules by present technology is limited to a few distinct methodologies. In most cases the most appealing methods from the standpoint of reaction rate and scale-up operate at elevated temperatures and produce generally lower yields of more complex molecules (Bigelow's "jet fluorination"); operate in anhydrous hydrogen fluoride which reacts with many organic moieties (Swart's Halogen Exchange Reaction and Simon's Electrochemical Process); utilize metal fluoride reagents which are expensive (AgF₂); or give incomplete fluorination with increasing complexity of the structure of the molecule to be fluorinated (CoF₃, KCoF₄). The low temperature direct fluorination process, on the other hand, is surface area dependent and utilizes mass transport to renew the surface of the solid phase hydrocarbon. Because the low temperatures slow the mass transport the reaction is unnecessarily slow although yields are usually quite high.

Our research is concerned with methods for producing and fluorinating at low temperatures fine uniform suspensions of solid particulates known as "sols." The method developed fluorinates "monodisperse" aerosol suspensions. The system described has the advantage of low temperature, solid phase, direct fluorination similar to the LTG process of Lagow, et. al. but is not dependent on low temperature mass transport to renew the reactant surface. This means that the reactions go in high yields and at an optimum rate limited by effective heat dissipation not mass transport.

Several of the above methods for the fluorination of hydrocarbons are

currently in commercial use. Each has varying advantages and disadvantages depending on the hydrocarbon and the functional group being fluorinated.

The Swarts reaction and other reactions involving halogen exchange require the preparation of the corresponding chlorocarbon derivatives prior to fluorination. Also fluorination becomes more difficult with increasing hydrogen or fluorine content on the carbon being fluorinated. Higher perchlorocarbons than the methanes and ethanes are difficult to prepare and have reduced reactivity. These factors are serious limitations for complex molecules where the chloro derivatives are not only difficult to prepare, but perfluorination or removal of all chlorines on a hydryl derivative requires more reactive reagents such as mercuric or silver fluorides.

The electrochemical fluorination method developed by Simons^{2,3,4,5} works very well for amines some carboxylic and sulfonic acids but rearrangements and β-cleavage occur for many acid and ether derivatives causing decreased yields.⁴ This method utilizes the electrolysis of hydrogen fluoride solutions of hydrocarbon at an electrode potential lower than that capable of producing elemental fluorine. It is intrinsically simple and therefore commercially appealing. The major drawback is the instability of many functional groups in anhydrous hydrogen fluoride. Aldehydes, ketones and esters have not been successfully fluorinated in synthetically useful quantities using the electrochemical technique.

The cobalt trifluoride method pioneered by Fowler and coworkers and other similar processes using high valent metal fluorides produce very good yields of saturated fluorocarbons with little fragmentation. The yields of F-alkanes produced by passing the vapor of n-alkanes over heated cobalt trifluoride were good but yields dropped sharply for more highly branched structures. A continuous reactor utilizing this process was designed and operated by these workers which produced F-alkanes and perfluorinated

lubricating oils. The primary limitations of this process are the need to recycle and regenerate the spent metal fluoride (CoF₂) using elemental fluorine; the inability to completely fluorinate many compounds especially those with highly branched structures; ⁷ and the inability to fluorinate many functional hydrocarbons.

Fluorination with elemental fluorine has generally developed into two distinct methodologies. The "Jet Fluorination" technique developed by Bigelow and coworkers 8,9,10 utilizes gaseous reactants in separate streams. rapid mixing, and then quick removal of products from the reaction zone to reduce fragmentation. The other method developed by Lagow and Margrave 11,12,13 utilizes "long" reaction times and the high dilution of fluorine with helium which also acts as a heat sink. A later development in this process by Lagow, Maraschin and Adcock 14,15,16,17,18 couples the high dilution and "long" reaction time with a low-temperature (LTG) reactor densely packed with "light" copper turnings. This method produces good yields of highly branched fluorocarbons 14,15 and is generally useful for the fluorination of hydrocarbon ethers, 16 esters, 17 acid fluorides 17,18 acid anhydrides 19 and cyclic amines. 20 The method shows some potential for other functional groups, such as primary amines and ketones. It, however, works well only for molecules with appreciable solid state volatility and crystallinity. Materials that form oils, glasses or have low solid state volatility give considerably lower yields than the 30-80% yields obtained when more nearly ideal molecules are fluorinated. It is also a batch process which is generally suitable only for small scale syntheses.

All of the previously mentioned methodologies have serious limitations and although some have been adopted for industrial scale production, clearly a simple, more nearly general fluorination method would be desirable. We would like to present what we believe is such a method.

Description of the Process

The significant successes of the LTG direct fluorination technique and the intrinsic simplicity of direct fluorination has led to a firm belief that a successful, general fluorination technique could be developed employing elemental fluorine. A critical analysis of the LTG reaction system produced a set of five conditions which we believe contribute to a high yield reaction. The conditions which we considered important are:

- (a) Fluorination of molecules in the crystalline state.
- (b) A very high reactant surface area exposed to gaseous fluorine.
- (c) Low initial temperatures.
- (d) High initial dilution of fluorine gas.
- (e) A highly efficient mechanism of heat dissipation.

The crystalline matrix reduces hydrocarbon radical recombinations when radicals are formed under "dilute" conditions. The crystalline matrix acts as an energy sink to dissipate reaction energies. A high reactant surface area promotes uniform attack by fluorine on all reactant molecules. Low temperatures reduce the vigor of reaction by an overall reduction in kinetic energy and by limiting the number of radical chain initiations. High initial dilution of fluorine reduces the overall reaction rate and reduces the likelyhood of simultaneous attack by two fluorine molecules or radicals on adjacent sites on a molecule which would increase the degree of fragmentation. Effective heat dissipation would prevent the formation of "hot spots" and prevent combustion from occurring. 21

These conditions, however, must be modified if one is to achieve high degrees of fluorination over a reasonable time span. The concentration of fluorine must be increased to maintain a good reaction rate as the reactant molecules become more highly fluorinated and a greater percentage of collisons are ineffective. It is also beneficial in this regard to increase

the temperature. Since these conditions directly conflict with the desired initial conditions their imposition must be separated in time or in space. The LTG system simply changes the applied temperature gradient and increases the fluorine concentration over time.

Separation of the perfluorination enhancing conditions from the initial conditions in space requires that the reactant be mobile. This mobile species may then be induced to pass through progressively warmer regions which have higher degrees of fluorine concentration. A gaseous reactant would be mobile, of course, but the desirability of limiting collisions between hydrocarbon radicals and thus limiting coupling reactions giving tars and oils dictates a condensed, preferably crystalline, phase. A liquid reagent stream does not allow for the uniform, rapid mixing of the very reactive gaseous elemental fluorine thus preventing uniform, controlled attack and substitution of fluorine at every C-H bond.

In order to achieve gas-like mobility and retain crystallinity it is necessary to produce extremely small solid particulates. These particulates may then be suspended and transported using a carrier gas. These particulates possess extremely high surface area which permits uniform attack by gaseous elemental fluorine on the suspended reactant. Extremely effective heat dissipation may be achieved by using helium as the carrier. Multiple collisions of the reactant particulates with the helium carrier gas molecules dissipate heat rapidly. Excess energy is continuously carried by the helium atoms to the walls of the reactor.

Principles of aerosol production are well developed. Our initial design ideas were developed from study of existing technology for producing aerosols which were developed primarily as an adjunct of atmospheric and industrial hygiene studies. Descriptive passages by N. A. Fuchs and A. G. Sutugin, ²²
R. D. Cadle ²³ and F. C. Goodrich ²⁴ describe the requirements of generators


capable of producing aerosols. A more recent paper by A. G. Sutugin describes a mixer type generator which is generally applicable to the problem of steady state aerosol production in a flow reactor. The major difference between our own independently developed design and that described by Sutugin is the subambient temperature capability of our design and its incorporation into a flow type reactor system.

The aerosol fluorination system designed to produce a controlled, continuous stream of aerosol particulates includes the following components (Figure 1). A bed of sodium fluoride heated to 850°C (A) sublimes highly dispersed NaF particles (average radius; 17.5 Å. 26) into the helium carrier gas. These particles serve as condensation nuclei for the hydrocarbon condensation. The carrier gas is chilled to near -196°C by passing through a liquid nitrogen cooled heat exchanger (B). The chilled carrier gas, helium in this embodiment, is mixed with a second gas stream containing the hydrocarbon vapor in a precise arrangement within the body of the generator (C). The hydrocarbon vapor in the stream produced by an evaporator device (D) will condense into aggregates around the sodium fluoride particles within the chilled carrier. The chilled aerosol is directly channeled into the reactor (E) where it is mixed with elemental fluorine in such a way as to produce uniform contact between the aerosol particles and elemental fluorine. The temperature of the reactor (E) is controlled by means of an integral heat exchanger which can provide variable temperatures from the cryogenic to the ambient range.

The aerosol generator system is of the evaporation-condensation type. It, however, seems likely that aerosol particulates generated by any mechanism; physical, chemical or mechanical; would work equally well. It is the high surface area created by extensive subdivision of aggregates that is essential to the process.

D

AEROSOL FLUORINATOR



Having created a mobile reactant it is possible to separate in space the conditions giving low fragmentation, i.e., high initial dilution of fluorine, low temperature; from those conditions leading to high degrees of fluorination; i.e., increased fluorine concentration and temperature.

Modular design of the system has allowed for the addition of staging components following the reactor (E). Each staging component consists of a module (F) and a "staging insert," (G). A series of modules (F') connected to the reactor thus provide for independently controlled temperature zones and the addition of "staging inserts," (G') which allow the independently controlled injection of additional elemental fluorine. Using these devices hydrocarbon or other molecules may be controllably fluorinated to any degree including perfluorination. It is also conceivable that other reagents besides elemental fluorine can be introduced in the later stages to achieve functionalization, etc. 27-29

The addition of modules and staging inserts may be continued indefinitely by insertion ahead of the end cap (H). Each stage may be modified
to provide for recycling of any or all of the various reacting species
although this is not practical at the lab scale. In the system shown
(Figure 1) a total of three staging inserts have been assembled giving in
effect a four-stage aerosol fluorination reactor in which fluorine can be
added in four independently controlled zones at three independently controlled temperatures. 30

In molecules which are exceptionally difficult to perfluorinate a heated coil (I') and/or a water cooled flow type photochemical reaction stage (J) following stage 4 (Figure 1) have been developed which significantly activate the elemental fluorine (or other reagent present in the reaction stream). The photochemical stage allows exceptionally high yields of perfluorinated products as well as much more efficient utilization of elemental fluorine.

The multistaged aerosol fluorination reactor achieves optimum control over the potentially violent direct fluorination reaction. It is possible to expose the unfluorinated reactant to a very dilute, even distribution of elemental fluorine at low temperatures. Furthermore the condensed phase of the aerosol particle distributes reaction heat evenly over a large number of molecules held in an ideally crystalline aggregate which may readily dissipate energy by multiple rapid collisions with helium gas. All of these effects serve to reduce the violence and heat accumulation which are primary concerns in direct fluorination. As the reactant molecule becomes more highly fluorinated and hence less vulnerable the aerosol aggregate is carried into regions of higher fluorine concentration, higher temperature and generally more rigorous conditions which tend to bring about higher degrees of fluorination. Finally the highly fluorinated product mixture may be introduced into the photochemical stage to achieve maximum fluorination.

This combination of conditions, which allows independent control of reactant concentration, stoichiometry, temperature and reaction time, is unique to the aerosol fluorination reactor. It is in effect a dynamic, variable-fluorine-concentration-gradient, variable-temperature-gradient reactor.

Description of the Experiments

Neopentane was purchased from K and K Laboratories, Inc. and was used as received. 1,4-Dioxane and Cyclohexane (Fisher) were dried over Linde 4-A molecular sieve before used. 2,2-Dimethyl-1,3-dioxolane was prepared by allowing a 1:2 molar mixture of acetone:ethylene glycol to reflux over L-4A molecular sieve in the presence of paratoluene sulfonic acid for several days. The filtered liquid was run slowly into saturated aqueous patassium carbonate. The separated organic (top) layer was dried over L-4A sieves and

fractionally distilled using a spinning band distillation apparatus. The pure product (b.p. 89.0-90.0°C, Lit 31 90.0°C) was collected in 11% yield although much more was collected as an apparent acetone azeotrope.

Elemental fluorine was purchased from Air Products Co. (97% Technical Grade, low oxygen content) in a cylinder containing 4.9 lbs \mathbf{F}_2 at 400 psig. IR spectra were run on a Perkin Elmer 257 grating spectrophotometer; Mass Spectra (Electron Impact and Chemical Ionization) were obtained on a Hewlett Packard 5980A Mass Spectrometer. 1 and 19 F NMR were obtained from the South Carolina Magnetic Resonance Facility, Columbia, South Carolina, operating under NSF-CHE78-18723. Elemental analyses were performed by Schwarzkopf Microanalytical Laboratory, Woodside, N.Y. Mass throughput values for neopentane 1,4-dioxane, 2,2-dimethyl-1,3-dioxolane and cyclohexane were calculated from empirical data which are presented in Table 1. Reactions with neopentane throughput at 4 mmoles per hour were run with the neopentane reservoir (D) at -63°C, He flow 101cc/min, throughput 0.29 g/hr, 4.0 millimoles/hr. Gas chromatographic separations were made on a Bendix Model 2300 gas chromatograph with multilinear programing and TC detection. The photochemical reaction stage consisted of ten meters of 0.015" wall, 3/8" ID FEP Teflon Tubing wrapped one layer around a 50mm x 390mm quartz immersion well containing a 550 watt (Hanovia) medium pressure mercury arc lamp and a second layer wrapped concentrically about an overlying 75mm pyrex tube. All FEP teflon tubing is maintained at approximately 20°-25°C by positive water circulation over all surfaces.

Neopentane Reactions: F/N-1 through 7 were run on the two stage modification of the aerosol reactor designated (S). This reactor consisted of the reactor with stage two insert, one staging module without insert followed by the end piece, H, and connecting tubing (3/8" copper tubing). The active volume of this reactor was 321 cm³ with average diameter of less than 0.5

inch. Reaction conditions are compiled in Table 2. Reaction times were approximated by dividing the active volume of the reactor by the combined flows of gas, principally helium.

Reactions F/N-8 through F/N-12 were run on the four stage modification of the aerosol reactor designated (T). This reactor consisted of the reactor with stage two insert, two staging modules each fitted with staging inserts followed by the end piece and connecting tubing. The active volume of this reactor was 268 cm³. The reduced volume is a result of the volume displacement by the second staging insert in the first staging module present in (S). Reaction conditions are compiled in Table 3.

Reactions F/N-13 through F/N-21 were run on the four stage modification (T) extended by the addition of a ten meter x 3/8" copper coil which increased the active volume of this reactor designated (U) to 771 cm³. A fifteen meter coil of 3/8 inch copper tubing [reactor designate (V)] and/or the photochemical module [reactor designate (W)/(X)] pictured in Figure 1 were the final extensions increasing the active volumes to 1524 cm³, 2108 cm or 1355 cm respectively. Their effect on reaction times are proportional to the volume changes however their effects on product distributions are not nearly so marked as that produced by the first coil but improvement does occur (UV off). Reaction conditions for reactor modification designate (U) are compiled in Table 4.

The left part of each table of reaction conditions (e.g. Table 4) lists the experimental values for the different variables used in a given reaction. These are: a) the flow of hydrocarbon, b) the flow of fluorine and c) the flow of inert gas, which consists of the main carrier, the hydrocarbon carrier and the fluorine diluent. Another variable, d) the temperature of the reactor, is only listed in the tables for the multistaging experiments, because it was kept constant at -65°C in all single-stage fluorination experiments.

The right part of each table lists reaction parameters which were calculated from two or more of the variables previously listed. The hydrocarbon to fluorine (h.c.: F_2) ratio needs no explanation.

The "stoichiometry" listed in the next column(s) is the fluorine-to-hydrocarbon-ratio divided by the number of hydrogens on the hydrocarbon molecule considered. This is more useful than the fluorine-to-hydrocarbon-ratio itself, for example:

- 1. To completely substitute one hydrocarbon molecule with \underline{n} hydrogen atoms \underline{n} F_2 -molecules are needed for complete fluorination.
- 2. If different hydrocarbons are compared, the "stoichiometry" gives a better picture of the true reaction conditions than the F_2 :h.c.-ratio itself. For example, a 24:1 F_2 :h.c.-ratio means a twofold excess of fluorine if cyclohexane or neopentane are considered (stoichiometry = 24:12 = 2), but a threefold excess of fluorine in the case of 1,4-dioxane (stoichiometry = 24:8 = 3).

The next column of each table lists the fluorine concentration for each reaction. This was calculated from the overall fluorine flow divided by the sum of all flows going through the reactor (x100). Thus it represents the concentration one would find at the end of the reactor (in multistaging experiments at the end of module #2), if no reaction would occur. The true fluorine concentration is certainly lower than this value, the error being larger for reactions with high hydrocarbon flows and low fluorine flows, while in reactions with low hydrocarbon throughputs and large excess of fluorine the true F_2 -concentration is probably close to the value listed. In multistaging experiments a gradient in fluorine concentrations was used. For some of the reactions an approximate fluorine concentration profile is given in the diagrams (Figures 2-7) for the product distributions of neopentane fluorinations.

FIGURE 2

NEOPENTANE PRODUCT DISTRIBUTIONS






FIGURE 3
NEOPENTANE PHOTOCHEMICAL PRODUCT DISTRIBUTIONS



NEOPENTANE PRODUCT DISTRIBUTION



NEOPENTANE PRODUCT DISTRIBUTION





FIGURE 6


1,4 - DIOXANE PRODUCT DISTRIBUTION




F/D - 12

Hydrocarbont 1.0 millimole/hour Fluorine; 480 millimole/hour

C4H8O2 + 60 x 8F2 22 min



37.2




Temperature Gradient




* Lower 1,4-Dioxane isomers decompose readily by loss of HF and Hydrolysis.

Hydrocarbon: 20 millimole/hour Fluorine: 480 millimole/hour $C_4H_8O_2+30\times8F_2$ 2.2 min With Ultraviolet Stage:

Temperature Gradient





+Ce

-50

2,2-DIMETHYL-1,3-DIOXOLANE PRODUCT DISTRIBUTION


$$\begin{array}{c|c} H_3C & O + CH_2 \\ H_3C & O - CH_2 \end{array} + F_2 \xrightarrow{\overline{AF}}$$




Hydrocarbon: 6.0 millimole/hour


Fluorine: 480 millimole/hour

 $C_5 H_{10} O_2 + 48 \times 10 F_2 = \frac{2.2 min}{30}$






Temperature Gradient




* Lower 2,2-Dimethyl-1,3-Dioxolane isomers decompose readily.




Fluorine: 480 millimole/hour

 $C_5 H_{10} O_2 + 24 \times 10 F_2 = \frac{2.2 \, \text{min}}{2.2 \, \text{min}}$

With Ultraviolet Stage:





74.5

Temperature Gradient



The last column of the tables for reaction conditions lists the reaction time. This means the average time a hydrocarbon particle travels from the aerosol generator to the product collecting trap, where it is frozen to -196°C and the reaction stops. This time was calculated from the volume of the reactor and the sum of flows through it. Of course this is only correct, if no hydrocarbon condenses inside the reactor at any time during a run. For the fluorinations of neopentane, especially those with high fluorine concentrations, this assumption is probably correct because of the high volatility of solid neopentane at -65°C.

Product mixtures from all neopentane fluorinations were treated with NaF/molecular sieves. To check the performance of every reaction, an analytical GLC-injection of a solution of the product mixture in CCl₄ was made on a 3/8" x 7 m fluorosilicone QF-1 column (Analabs). The temperature program used is the same as for product separations from LTG-neopentane fluorinations: $T_1 = 25$ °C for 10 min; $R_1 = 10$ °/min; $T_2 = 75$ °C for 10 min; $R_2 = 50$ °/min; $T_3 = 125$ °C for 24 min.

To identify the unknown partially fluorinated neopentanes, products from reactions F/N-1, 11, 14, 17, 18 and 19 were separated preparatively by GLC to obtain samples for NMR-measurements (Tables 5 and 6). Corresponding products from reactions F/N-2, 4, 5 and 13 were separated for mass spectral investigations (Table 7).

Identical samples from the different reactions (as certified by IR) were combined to obtain sufficient material for spectral investigations and elemental analysis of some products since every two hour reaction run with a hydrocarbon flow of 1 mmole/h gave only 100 to 300 mg of crude product mixture.

Only one fraction from the first GLC-separations was further separated. The QF-1 peak between 33 and 35 min retention time (NF, NO, NP) was

separated on a phenyl-methylsilicone rubber column SE-52 with the following temperature program: $T_1 \approx 70^{\circ}\text{C}$ for 10 min; $R_1 = 25^{\circ}/\text{min}$; $T_2 = T_3 = 120^{\circ}\text{C}$ for 7 min. Compounds NS and NT occurred in some reactions as a difficult to separate mixture but could be produced nearly pure by stoichiometric control. All purified products prepared for elemental analysis were assayed on the SE-52 column to establish purity after initial QF-1 column GLC purification.

The product distributions for some typical reactions were estimated by determining the areas of peaks in the GLC-traces (Table 8). The reactions chosen for this were: F/N-1, F/N-6, F/N-7, F/N-11, F/N-16, F/N-17, F/N-20 and F/N-21. Table 8 lists these product distributions. Since no decomposition during work-up was observed, and all materials were volatile and soluble in CCl₄, these values should represent something close to the real product distribution for the neopentane fluorinations under different reaction conditions. Thus these distributions could be used to graphically show the effect of reaction parameters on fluorination efficiency. Compounds are ordered NA through NT on the basis of their Fluorosilicone QF-1 retention time (Table 9).

Photochemical Neopentane Reactions: Procedures for conducting the photochemical neopentane reactions were very similar to the "dark" reactions. As previously was the case, the particulate furnace, cooling jackets, carrier flows, fluorine flows and where used the photochemical cell were allowed to come to equilibrium-readiness before any hydrocarbon was admitted to the system. The details of the photochemical experimental conditions for neopentane [PF/N-1 through PF/N-7, reactor configuration (X)] are listed in Table 10. A set of control runs (NPF/N-4 through NPF/N-7) were run under identical conditions except the photochemical lamp was off. The product distributions of the control runs are illustrated along with the photochemical runs on Figures 4 and 5.

The problems of mass balance in the aerosol system are complex. Throughputs are determined empirically by collecting the output of the hydrocarbon evaporator over several half hour periods. A calibration curve is developed as a function of carrier flow versus mass output for a given reservoir temperature. Except for those reactions giving only a few products, yields are tedius, time consuming and prone to experimentalist technique losses. Product distributions as given can be deceiving in that they are yields relative to other products. Generally output masses are about two thirds of those expected even when no fluorine is used. This points out one of the difficulties of aerosol particulates, i.e., their capture. Yields of the photochemical experiments leading to a few products are given. Reaction PF/N-7 yields 0.54g F-neopentane for a 5 hour, one millimole per hour run. The oretical yield estimate 5 millimoles, 1.44g, a yield of 38%.

Products from the aerosol fluorinations of neopentane were identified on the basis of their 19 F (Table 5) and 1 H (Table 6) spectra, CI and EI mass spectra, elemental analysis and IR spectra (Table 7). Assignments are based mainly on the NMR spectra, because the chemical shifts for fluorines as well as hydrogens on the differently fluorinated methyl groups (i.e. CH_3 , CH_2 F, CHF_2 , CF_3) are very characteristic; their couplings are relatively simple, and integrations also help to clearly identify products.

Mass spectral data for the partially fluorinated neopentanes are not conclusive, because (except for mono-fluoro- and difluoroneopentane) no molecular ion or molecular ion minus fluorine was found.

1,4-Dioxane Reactions: Although many reactions involving all levels of fluorination of 1,4-dioxane were performed, 30 the instability of the polyfluoro-1,4-dioxanes, especially the trifluoro species, prevented as detailed an examination of product distributions as was detailed for neopentane.

Only those reactions producing high degrees of fluorine substitution were

amenable to even near quantitative workup. For these later runs reactor configuration (V) was used for the initial "dark" reaction runs and reactor configuration (X) was used for the photochemical runs and their controls (Table 11). In each case the products collected were condensed into a reservoir containing sodium fluoride pellets and L-4A molecular sieves separated by a one inch layer of "light" copper turnings and allowed to stand at room temperature overnight. The products remaining were vacuum line fractionated through -78°C, -131°C and -196°C traps. The -78°C and -131°C traps were combined and subjected to gas chromatographic separation on the fluorosilicone QF-1 column described earlier at a constant temperature of 125°C. The -196°C trap, usually containing only a few milligrams of very volatile material was discarded.

Products from the fluorinations of 1,4-dioxane have been characterized by their ¹⁹F and ¹H NMR spectra, CI and EI mass spectra and IR spectra. As is also the case for partially fluorinated cyclohexanes, ¹H NMR spectra of partially fluorinated 1,4-dioxanes are very complex due to coupling across the ring. But again signals of CH₂ groups and signals of CFH-groups can be clearly distinguished and their relative integrations give information about the extent of fluorination. ¹⁹F NMR spectra are somewhat simpler. In addition, ¹⁹F NMR spectra for both the fully and partially fluorinated 1,4-dioxanes containing four or more fluorine atoms have been described in detail in the literature making characterization much simpler. ^{7,32}

Mass spectra of partially fluorinated 1,4-dioxanes are also very useful for identification; EI mass spectra usually show ${\rm C_2F_nH_{4-n}}$ -masses with very high intensities, from which the number of fluorine atoms on each side of the ring can be determined. This information allowed the product distribution graphs to be readily constructed for reactions involving the more highly fluorinated 1,4-dioxanes that may be cleanly separated by single glc

injection (Figure 6). Reaction PF/D-1 produced 0.7963g of \underline{F} -1,4-dioxane for a 3 hour-2 millimole per hour run. Theoretical yield estimate for 6 millimoles \underline{F} -1,4-dioxane is 1.33g a yield of 57%.

Cyclohexane Reactions: Again many reactions at virtually all levels of fluorination were conducted with cyclohexane. 30b The highly complex 1H and 19 F NMR spectra due to extensive coupling and conformational equilibria have been to a great extent worked out in the literature. 33-35 The difficulty in providing meaningful product distributions arises from the difficulties in obtaining quantitative separation of the various products which required use of up to three, generally two, different glc columns on each complex fraction. For this reason only the photochemical results for conditions leading to perfluorination are reported (Table 11). The product collected was almost pure F-cyclohexane in 30% yield based on the average throughput of two millimoles per hour.

2,2-Dimethyl-1,3-dioxolane Reactions: Only reactions leading to high degrees of fluorination are listed in Table 11. Characterization of various hydryl-F-2,2-dimethyl-1,3-dioxolanes, are given in the literature. The product distributions (Figure 7) represent only those seven major components (\sim 70% total) which are "stable" to the NaF/L-4A treatment and do not pass a -131°C trap at 10⁻³ torr. The product distributions (Figure 7) are estimates based on gas chromatographic assay on Fluorosilicone QF-1 using the temperature separation program $T_1 = -8$ °C for 8 min; heating 8°C/minute, $T_2 = 144$ °C for 20 minutes. The photochemical fluorination resulted in collection of 1.1593g of material at an average hydrocarbon throughput of 2 millimoles per hour for three hours. GLC purification of the product gave 0.87g (74.5%) pure F-2,2-dimethyl-1,3-dioxolane resulting in a yield estimate of 51.4%.

Results and Discussion

Neopentane, 1,4-dioxane, cyclohexane and 2,2-dimethyl-1,3-dioxolane have all been successfully fluorinated by the aerosol process. Neopentane, however, was chosen as the model compound for detailed study of the reactor system for several reasons. Five of the most important reasons are enumerated below:

- i) Partially fluorinated neopentanes are stable, since elimination of HF, which is very favorable in partially fluorinated dioxanes and dioxolanes, cannot occur; γ -elimination of HF to form a 3-membered ring should not occur under work-up conditions.
- ii) Partially fluorinated neopentanes have a higher volatility and solubility in CCl₄ than similar fluorinated cyclohexanes or dioxanes, thus facilitating work-up and giving a more accurate product distribution.
- iii) There are not as many different isomers. Also different conformations for a given degree of fluorination such as occur in dioxane or cyclohexane are not a problem. Therefore the influence of reaction parameters should be more easily seen directly from the product distribution.
- iv) Gas chromatographic separation in one step has proved to be possible, so that the GLC-chromatogram could be used for quantitative estimation of product distributions.
- v) Four of the most highly fluorinated neopentanes (i.e. <u>F</u>-neopentane, undecafluoroneopentane, decafluoroneopentane and nonafluoroneopentane) were known from gradient reactor reactions, thus making it easier to judge the "success" of a fluorination. 14,37

Initially twenty-one non-photochemical reactions with neopentane were run and the results compared. In each of these reactions variables such as carrier flow, fluorine concentration gradient, reaction time and hydrocarbon mass throughput were changed. Repetative runs were made, generally only one

variable at a time was changed so as to ascertain its effect on product distributions. In none of the cases outlined in Tables 2-4 was the reactor or reaction uncontrolled or perceptively violent even in those runs involving fluorine flows exceeding 200 cc/minute (480 mmoles/hr). The product distributions for neopentane as a function of the fluorine concentration gradient in these initial runs are given in Figure 2. In this diagram isomers are combined to illustrate the degree of fluorination obtained as a function of fluorine concentration, concentration gradient, relative F,:h.c. stoichiometry and reaction time. It is quite evident that a gaussian distribution of products is approached. This is seen most clearly in reactions F/N-1, F/N-11, F/N-17 and F/N-20. Significant deviations however occur for certain sets of conditions. The most readily explicable is that illustrated by F/N-21, Figure 2. In this reaction only the hydrocarbon throughput was increased (four-fold) relative to F/N-20. This effect, a compression of the maximum toward lower substitution, is undoubtedly due to fluorine concentration gradient changes as the increased hydrocarbon throughput consumes additional fluorine. The molar amount of fluorine is not at every point much greater than the molar amount of hydrocarbon. This effect is reproducible.

Preferential Fluorine Reactivity

The preceding discussion indicates that fluorination occurs stepwise under our conditions and that product distributions with regard to degree of fluorination should be readily explainable on simple statistical and kinetic grounds. The question which remains is whether each degree of fluorination exhibits a distribution of isomers based on simple statistics. In this regard it became necessary to identify each possible isomer, its statistical weight based upon the assumption of stepwise fluorination, and the comparison of the theoretical with the experimental distribution of

isomers. Because of the nature of the aerosol process, the assumption that only effects due to statistical weighting or internal directive effects should be important is a defendable one. The basic process involves finely dispersed hydrocarbon particulates in a gaseous helium matrix which are subjected to diffusion controlled attack by gaseous fluorine. Fluorine is injected evenly along the reactor length so as to produce a dynamic fluorine concentration gradient which is ideally at a steady state. Fluorine concentration should remain constant at any given point along the reactor length. This unique set of conditions roughly approximates the conditions produced by a molecular beam apparatus where two reactants intersect and react in a manner governed by condition dependent statistical probability as operated on by the intrinsic reactivities of the reactants themselves. In the aerosol system the intersecting points are random; diffusion controlled, and compound permitting only a statistical treatment and an approximate one at that. It should however be possible to achieve a qualitatively valid comparison between experiment and theory.

For this comparison the products of eight selected reactions of neopentane with elemental fluorine were separated by gas chromatography, and analysed by ^1H and ^{19}F nmr and EI and CI mass spectrometry. The isomer distributions are based on relative peak areas of the thermal conductivity chromatograms.

The statistical probability of isomers based on the assumption of stepwise substitution are illustrated in Figure 8. In Figure 8 the statistical probability of each isomer based on stepwise substitution is indicated. In each case the probability of the most symmetrical isomer is underlined. The experimentally determined isomer distribution (which is the average of three to five reactions) was determined by comparison of relative peak areas of the gas chromatographed products. In all cases the most unequivocal

Figure 8

The Statistical Probability of Isomers Based on Stepwise Substitution of Hydrogens by Fluorine

CH CH 1 3	Monofluoroneopentane: CH ₂ F UCCOUNTY	Difluoroneopentanes: $\begin{array}{ccc} \text{CH}_{F} \\ \text{L}_{C} \\ \text{CH}_{F} \end{array}$	CHF 1 2 1
 	n3c-c-n3 CH3	$\frac{1}{3}$ $\frac{1}{C}$ $\frac{1}{C}$ $\frac{1}{3}$	racena CH ₃
Statistical Probability: Experimental Distribution:	1,000	$\frac{0.8182}{0.8991}$	0.1818 0.1157

•	CHF ₂ + H ₃ C-C -CHF ₂ CH ₃	0.1091 0.0245
	$\begin{array}{c} \operatorname{CH}_2^{\mathrm{F}} \\ 1 \\ 2 \\ -\operatorname{C-C-CH}_2^{\mathrm{F}} + \\ \operatorname{CH}_2^{\mathrm{F}} \end{array}$	$\frac{0.1636}{0.1411}$
nes:	+	
Tetrafluoroneopentanes:	$CHF_2 = \frac{CHF_2}{13}$ $H_3C-C-CH_2F$ CH_2F	0.6545 0.8344
Tet	†	
	CF ₃ 1 1 C-C-CH ₃ CH ₃	0.0182
	$\frac{\text{CHF}_2}{1}$ + $\frac{1}{13}$ C-C-CH ₂ F + $\frac{1}{13}$ C-CH ₃	0.4909 0.4075
ines:		
Trifluoroneopentanes:	$\begin{array}{c} cH_2F\\ 1\\ 1\\ C-C-cH_2F\\ 1\\ CH_2F \end{array}$	0.4909 0.5925

	CF ₃	$^{-}$ H ₃ C-C-CHF ₂ \rightarrow	сн ₃	0.0455	1
	CF ₃	+ H_3 C-C-C H_2 F +	$ch_2^{\mathbf{F}}$	0.1364	1
	$\frac{\text{CHF}}{1}$	FH2C-C-CH2F	$\mathrm{ch}_2^{\mathrm{F}}$	0,4091	1,0000
ines:		+			
Pentafluoroneopentanes	CHF ₂	$$ H_3 C-C-CHF ₂	$c_{ m H_2}^{ m F}$	0.4091	!
		•			
	$_{1}^{\mathrm{CF}_{3}}$	$^{\mathrm{H}_3\mathrm{C-c-cH}_2\mathrm{F}}$	ĊH ₃	0.0727	1

Figure 8 (Continued)

Hexafluoroneopentanes:	es:	!		į
CHF ₂		CF.		CHF -
FH, C-C-CHF,	+	н ₃ с-с-сн ₂ + н ₃ с-с-сн	+	н 3с-с-сн
1 E E		CHCF		CHF

†	pentanes CHF ₂
CF3 H ₃ C-C-CF ₃ CH ₃ 0.0065	octafluoroneopentanes CF3 CHF
+	Ō
CF ₃ FH ₂ C-C-CH ₂ F CH ₂ F 0.1169	CF ₃
+	
CHF ₂ H ₃ C-C-CHF ₂ CHF ₂ 0.1169	CF ₃
+	
CF3 H ₃ C-C-CHF ₂ + CH ₂ F 0.2338	CF3
+	es:
CHF ₂ FH ₂ C-C-CHF ₂ CH ₂ F CH ₂ F 1.0000	ptafluoroneopentanes: CHF,

results are those where two or more isomers are isolated. However single isomer products may be considered at least five fold probably ten fold larger than any non-detected, non-isolated isomers.

The results indicate that substitution is near statistical until one reaches the pentafluoroneopentane. At this point only the most symmetrical isomer is isolated. This would indicate that a hydrogen of a CH3 group is more reactive than a hydrogen of a CH₂F or CHF₂ group. At the next step only one hexafluoroneopentane is isolated indicating that a hydrogen on a $\mathrm{CH}_2\mathrm{F}$ is more readily substituted than a CHF_2 however this is also statistically the predicted major isomer. The more definitive case comes at the heptafluoroneopentane where again the only isomer isolated is the most symmetrical. However here the unsymmetrical $(CF_3)C(CH_2F)_2(CHF_2)$ isomer is of equal probability. This is a more convincing case for the greater reactivity of hydrogens on $\mathrm{CH}_2\mathrm{F}$ relative to CHF_2 . The octafluoroneopentane case also supports this contention. The theoretical distribution of the unsymmetrical $(CF_3)C(CHF_2)_2(CH_2F)$ isomer to the symmetrical $C(CHF_2)_4$ is 4:1 however the experimental distribution is closer to 1:1. Again at the nonafluoroneopentane the lowered reactivity of the CHF, group is indicated in that the ratio of isomers $(CF_3)_2C(CHF_2)(CH_2F)$ to $(CF_3)C(CHF_2)_3$ theoretically is 1:1 however the experimental ratio is close to 1:4 with the symmetrical isomer predominating.

Although the experimental numbers themselves are of little theoretical value the experimental isomer ratios compared to the theoretical isomer ratios indicate unequivocally that the reactivities of hydrogen atoms to attack by elemental fluorine can be altered and that hydrogens are not always indiscriminately attacked by fluorine in a purely statistical way. The apparent order of hydrogen reactivity is $CH_3 > CH_2 F > CHF_2 >> CF_3$. This order not only parallels the order of steric accessibility of the hydrogen atoms

but also parallels the expected order of electron density on the hydrogens. The latter effect if controlling probably indicates that fluorine prefers the more electron rich hydrogens. This at least suggests that selectivity in a molecule might be achieved by altering the electron density of the carbon bearing the hydrogen.

Photochemical Assisted Fluorinations

The addition of the photochemical reaction stage to the aerosol fluorinator now permits significantly better utilization of elemental fluorine at least in the low degree of fluorination range. The comparison of PF/N-1 (Figure 3) with F/N-1 (Figure 2) demonstrates that almost a 12 fold decrease in fluorine excess is possible while achieving virtually the same product distribution and similar yields. More importantly however the photochemical stage allows the achievement of high degrees of perfluorination although at the expense of some fragmentation. Yields are still quite high for those "expected" for an elemental fluorine reaction and certainly one utilizing photochemical activation in the final stages. The key to molecular integrity is obviously the fact that molecules entering the gradient photochemical cell are already highly fluorinated (Figures 4 and 5) and are therefore more robust and capable of resisting fragmentation under vigorous attack by both molecular and atomic fluorine. It is significant to note that the photochemical cell has not in nearly a year of use become befouled and to the contrary looks almost as good as the day it was initiated. A ultraviolet transmission spectrum of the 0.015" FEP Teflon film shows that its absorbance curve is near zero and flat until it shuts off at 224 nm in the ultraviolet. It is however of utmost importance to keep the polymer wall near 25°C as it begins to loose its structural rigidity about 50°C forming kinks in the smooth coil. A word of caution is in order, since

atomic fluorine is produced in the photochemical cell excessive temperatures may cause the FEP Teflon to be attacked with disasterous results at the higher fluorine flows.

The higher fluorine flows produce anomolous results in the product distributions of the neopentane photochemical reactions. Unlike the "dark" reactions which give a successively higher degree of fluorination with increasing concentration, the photochemical reaction begins to produce F-Neopentane. The relative proportions of F-neopentane and lower fluorinated species remain near constant as the fluorine concentration is increased. This effect may be due to increasing fragmentation reducing overall yields which do decrease somewhat.

Survival in the photochemical stage may be dependent on previously achieving a particular degree of fluorination for a given residence time in the photochemical reactor for a given fluorine concentration. The threshold level may be related to fluorine radical chain propagation occurring due to concentration effects. Some support for this may be seen in PF/N-6 where lower component survival rises dramatically when the main carrier is increased three fold. Obviously a good deal of optimization of conditions remains to be done before much more can be said about the photochemical system.

The fluorination of 1,4-dioxane dramatizes the effectiveness of the photochemical stage. The crude product collected from the reactor is better than 90% pure F-1,4-dioxane in yields approaching sixty percent. The extremely difficult direct fluorination of cyclohexane to perfluorocyclohexane can be accomplished in yields exceeding thirty percent and a product purity in excess of ninety percent direct from the reactor. The low yields are due to tar formation in stage one which we should be able to eliminate by reducing the fluorine concentration gradient at this stage.

Absence of Hydrogen Fluoride Solvolysis

The direct fluorination reaction produces a molecule of hydrogen fluoride for every hydrogen substituted. It was of interest to determine whether acid catalysed cleavage would occur in the reactor system to an appreciable extent. The very acid sensitive ketal, 2,2-dimethyl-1,3-dioxolane was chosen for this determination. The results indicate that HF solvolysis of such groupings is not a problem. It was possible to produce fluoro analogs of the 1,3-dioxolane in very good yields with almost no evidence of HF solvolysis. The photochemical perfluorination went uneventfully and actually produced higher overall yields than the 1,4-dioxane. Whether this lack of solvolysis is general will, of course, require reaction of many different compounds and different functionalities.

Summary

The multistaged aerosol fluorination reactor achieves optimum control over the potentially violent direct fluorination reaction. This system meets all of the criteria enumerated earlier which we, by experience, believe contribute to high yield direct fluorination reactions. It additionally has other distinct advantages in that the degree of fluorination may be controlled; it is a flow process; the process does not depend on the physical properties of the reactant to be fluorinated; reactant throughputs may be varied over a considerable range for a given design; fluorine concentration and temperature conditions may be taylored to the reactivity of the reactant; and most importantly the observation of non-statistical substitution effects suggests that this system might permit the elusive achievement of selectivity in direct fluorinations.

TABLE 1

MASS THROUGHPUT FOR HYDROCARBONS IN THE AEROSOL SYSTEM

HELIUM CARRIER flow-rate [cc/min]	MASS OF HYDROCARBON [mg/h]	MASS THROUGHPUT [mmol/h]
NEOPENTANE: (a)		
63.5	38.2	0.53
84.5	60.6	0.84
98	70.8	0.98
100	71.8	1.00
110	94.6	1.31
126	103.4	1.43
174	115.4	1.60
NEOPENTANE: (b)		
43	150	2.0
101	290	4.0
CYCLOHEXANE: (c)		
8	60	0.71
14.5	87.3	1.04
43.5	245.8	2.92
102	523.8	6,22
2,2-DIMETHYL-1,3-DIOXOLAN	E: (d)	
19	200	1.96
32	410	4.02
64	630	6.18

Hydrocarbon Reservoir Tem erature: (a) -78° C, (b) -63° C, (c) 0° C, (d) 39° C

TABLE 2

REACTION CONDITIONS FOR AEROSOL FLUORINATIONS OF NEOPENTANE IN A TWO-STAGE REACTOR (S)

Ref. No.	hydrocarbon h.c. main F ₂ -flow F ₂ dil. flow carrier carrier [cc/min] He flow [mmoles/h] [cc/min] st. 1 st. 2 Σ [cc/min]	h.c. carrier [cc/min]	main carrier [cc/min]	F2- [CC St.]	F ₂ -flow [cc/min] lst. 2	ω	F ₂ dil. He flow [cc/min]	hc:F2	stoi	stage	netry	stoichiometry % F ₂ stage at end of 1 2 E reactors.	reaction time [sec]
F/N-1	~	101	2000	5	ı	5	5 100 + 20 1:12	1:12	Н	1	~	0.1	3.7
F/N-2	~	101	2500	5	ı	7	20 + 20	1:12	7	1	Н	0.19	7.3
F/N-3	-1	101	2500	10	ſ	10	20 + 20	1:24	7	1	2	0.38	7.3
F/N-4		101	2500	5	5	10	20 + 20	1:24	7	۲	2	0.38	7.3
F/N-5	-	101	2500	S	15	20	20 + 20	1:48	ī	3	4	0.75	7.2
F/N-6		101	2500	20	f	20	20 + 20	1:48	4	ı	7	0.75	7.2
F/N-7	7	101	2500	20	20	40	20 + 20 1:96	1:96	4	4	∞	1.5	7.2

TABLE 3

REACTION CONDITIONS FOR AEROSOL FLUORINATIONS OF NEOPENTANE IN A FOUR-STAGE REACTOR (T)

Ref. No.	hydrocarbon flow	h.c. carrier	main carrier	F2		stag	cc/m:	·	F ₂ dil He flow
	[mmoles/h]	[cc/min]	[cc/min]	1	2	3_	4	Σ	[cc/min]
F/N-8	1	101	2500	20	20	-	-	40	4 x 20
F/N-9	1	101	2500	20	20	20	_	60	3 x 20 + 10
F/N-10	1	101	2500	20	20	20	20	80	4 x 20
F/N-11	1	101	2500	20	20	20	20	80	4 x 20
F/N-12	1	101	2500	20	20	20	20	80	4 x 20

continued below

n-E V	1 17	i	n s	tag	•	Σ	$% F_2$ at end of	reaction time	temperat modu	les	
Ref. No.	hc:F ₂	1		3	- 4		react. syst.	[sec]	reactor	#1	#2
F/N-8	1:96	4	4	-	-	8	1.5	5.9	- 65	-60	-60
F/N-9	1:144	4	4	4	-	12	2.2	5.9	- 65	-60	- 60
F/N-10	1:192	4	4	4	4	16	2.9	5.8	- 65	-60	-60
F/N-11	1:192	4	4	4	4	16	2.9	5.8	-65	-60	-30
F/N-12	1:192	4	4	4	4	16	2.9	5.8	- 65	-60	-30

TABLE 4

REACTION CONDITIONS FOR AEROSOL FLUORINATIONS OF NEOPENTANE IN A FOUR-STAGE REACTOR + COPPER COIL (U)

Ref. No.	hydrocarbon flow [mmoles/h]	h.c. carrier [cc/min]	main carrier [cc/min]	F ₂ flows [cc/min] in stage 1. 2 3 4 Σ	F ₂ dil. He flow [cc/min]
F/N-13	1	101	2500	20 20 20 20 80	4 x 20
F/N-14	1	101	2500	20 20 20 20 80	4 x 20
F/N-15	1	101	2500	20 20 20 20 80	4 x 20
F/N-16	1	101	1250	20 20 20 20 80	4 x 20
F/N-17	1	101	600	20 20 20 20 80	4 x 10
F/N-18	1	101	600	20 20 40 40 120	4 x 5
F/N-19	1	101	600	20 20 60 60 160	4 x 10
F/N-20	1	101	400	20 20 60 100 200	4 x 5
F/N-21	4	101	400	20 20 60 100 200	4 x 5

	tempe	ratur modul]				hiom	-	•		reaction time
Ref. No.	reactor	#1	#2	coil	hc:F ₂		2	3	4	Σ	% F ₂	[sec]
F/N-13	- 65	-60	-30	RT	1:192	4	4	4	4	16	2.9	16.8
F/N-14	- 65	-30	0	+45	1:192	4	4	4	4	16	2.9	16.8
F/N-15	- 65	-30	0	+45	1:192	4	4	4	4	16	2.9	16.8
F/N-16	- 65	-30	0	+45	1:192	4	4	4	4	16	5.3	30.6
F/N-17	- 65	-30	0	+45	1:192	4	4	4	4	16	9.7	56.3
F/N-18	- 65	-30	0	+45	1:288	4	4	8	8	24	14.3	55
F/N-19	- 65	-30	0	+45	1:384	4	4	12	12	32	17.25	51.3
F/N-20	- 65	-30	0	+45	1:480	4	4	12	20	40	27.7	64.1
F/N-21	-65	-30	0	+45	1:120	1	1	3	5	10	27.7	64

TABLE 5

19 F NMR DATA OF FLUORINATED NEOPENTANES

			CF3	~	CF ₂ H	H.	CF	\mathtt{CFH}_2	
			J J	ה	8	ה	8	ָר ר	
Formula	Ref. No.	Structure	[ppm] a)	[Hz]	[ppm] a)	[Hz]	[ppm] a)	[Hz]	Integration ratios
C ₅ H ₁₂	*	C(CH ₃),							
C ₅ H ₁ 1F	8	(CH ₃) ₃ C-CFH ₂					222.7	(t) 46	
CsH10F2	Ę	(CH ₃) ₂ C(CFH ₂) ₂			•		227.8	(t) 50.9	
CsH10F2	NF.	(CH ₃) ₃ C-CF ₂ H			~128 ^{b)}	$^{\sim}128^{b}$ (d) 57.1			
$C_{S}H_{9}F_{3}$	ŅÓ	(CFH ₂) ₃ C-CH ₃			•		234.6	(t) 49.6	
C ₅ H ₉ F ₃	NK.	$(CH_3)_2C(CFH_2)(CF_2H)$			∿131 ^{b)}	(d) 53.4	~228 ^{b)}	(t) 45.8	d:t √ 2:1
C ₅ H ₈ F ₄	SN	C(CFH ₂),					240.1	(t) 45.8	
C ₅ H ₈ F ₄	NN	(CH ₃) ₂ C(CF ₂ H) ₂			129.2	(d) 53.4			
$C_{sH_BF_4}$	NO NO	$(CFH_2)_2C(CF_2H)(CH_3)$			132.7	(d) 53.4	236.3	(t) 45.8	d:t % 1:1
$C_5H_2F_5$	NT	(CFH ₂) ₃ C-CF ₂ H			131.1	(d) 53.4	241.1	(t) 45.8	d:t √ 2:3
$C_{5}H_{6}F_{\gamma}$	NR	(CFH202C(CF2H)2			130.1	(d) 48.8	242.4	(t) 48.8	d:t % 2:1
C ₅ H ₅ F,	NP	(CF ₂ H) ₃ C CFH ₂			129.1	(d) 53.4	243.8	(t) 45.8	d:t = 6.8:1
C ₅ H ₄ F ₈	NK	C(CF2H),			128.4	(d) 53.4			
C ₅ H ₄ F ₈	NI	$(CF_2H)_2C(CF_3)(CFH_2)$	8.99	(s)	129.3	(d) 51	244.4	(t) 41	s:d:t = 3:4:1
C ₅ H ₃ F ₉	HN	(CF ₂ H) ₃ C-CF ₃	64.5	(s)	127.8	(q) 21	,	.	s:d x 1:2
C ₅ H ₃ F ₉	NG	$(CF_3)_2C(CFH_2)(CF_2H)$	66.57 ^{c)}	(b)	130.1 ^{c)}	(d) 52.2	240.4 ^{C)}	(t) 45.6	
CsH2F10	NE	$(CF_2H)_2C(CF_3)_2$	9.49	(d)	127.29	(d) 54.5			
CsHF11	NC	(CF3)3C-CF2H	65.4°	(t)	125.7	53			
CsF12	NB	C(CF ₃),	65.42 ^c	(s)					

Chemical shifts Ø [in ppm] are relative to internal CFCl3; since resolution of the spectra was not very high, only the large geminal F-H couplings were observed.

b) Chemical shift values measured from spectra.

Data from LTG-products, chemical shifts are measured from spectra. See References 14 and 37. (၁

TABLE 6

1 NMR SPECTRA OF FLUORINATED NEOPENTANES^{a)}

			СН3		Ö	CH ₂ F	Ö	CHF ₂	
Formula	Ref. No.	Structure	δ [ppm]	_Ј в) [Hz]	ہ [ppm]	_ј ь) [нг]	ô [ppm]	_Ј в) [Hz]	Integration Ratios
C3H12	*	C(CH ₃),	0.94						
C ₅ H ₁₁ F	QN	(CH ₃) ₃ C-CFH ₂	96.0	(d) 1.7	4.0	(d) 48			
CsH10F2	NL	(CH ₃) ₂ C(CFH ₂) ₂	96.0	(t) 1.8	4.2	9.74 (b)	;	-	t:d = 3:2
CsH10F2	NF.	(CH ₃) ₃ C-CF ₂ H	66.0	(d) 1			رم ^ر ہ		
$C_sH_9F_3$	Ņ	(CFH ₂) ₃ C-CH ₃	1.05	(q) 1.7	4.4	(d) 47.1			g:d = 1:2
$C_5H_9F_3$	NK •	$(CH_3)_2C_9CFH_2)(CF_2H)$	1.06	(m) < 1	4.25	(d) 47.1	5.67	(t) 56.6	m:d:t % 7:2:1
CsHgF.	SN	C(CH ₂ F) ₄			9.4	9.94 (b)			
CsHaF4	NN	$(CH_3)_2C(CF_2H)_2$	1.3				92	(t)	s:t ∿ 3:1
C.H.F.	NO	$(CFH_2)_2C(CF_2H)(CH_3)$	1.1		e)	(m)	5.8	(t) 55.7	s:m:t % 3:4:1
CsH,Fs	NT	(CFH ₂) ₃ C-CF ₂ H			99*4	9.94 (b)	0.9	(t) 54.7	d:t % 6:1
C ₅ H ₆ F ₆	NR	$(CFH_2)_2C(CF_2H)_2$			4.7	7.94 (b)	6.1	(t) 54.4	d:t = 2:1
C ₅ H ₅ F ₇	d.	(CF2H) 3C-CFH2			6.4	(d) 46.1	6.2	(t) 54.2	
CsH4F8	Ä	C(CF ₂ H),					6.3	(t) 54	
CsH4F8	NI	$(CF_2H)_2C(CF_3)(CFH_2)$			4.95	97 (P)	6.24	(t) 54	
CsH3F9	NH	(CF ₂ H) ₃ C-CF ₃					6.3	(t) 53	
$C_5H_3F_9$	NG	$(CF_3)_2C(CFH_2)(CF_2H)$			4.92	(d) 45.6	6.31	(t) 52.2	f)
$C_5H_2F_1o$	NE	$(CF_3)_2C(CF_2H)_2$					6.21	(t) 52.2	f)
CsH1F11	NC	(CF3) 3C-CF2H					6.255	(t) 54.5	f)
CsF12	NB	C(CF ₃)4							

Chemical shifts & [in ppm] are relative to TMS; they were calculated by assuming that the residual proton on CDCl₃ occurs at 7.26 on &-scale.

d = doublet, t = triplet, q = quadruplet, m = multiplet (Note: only basic splittings are given).
This signal is a very weak triplet, which does not appear in the print out.
from: F. A. Bovey, "Nuclear magnetic resonance spectroscopy," 1969.

F G G C E

data from LTG products, see References 14 and 37. complex multiplet between 4.3 and 4.6 ppm.

TABLE 7

IR MASS SPECTRA AND ELEMENTAL ANALYSIS FOR PARTIALLY FLUORINATED NEOPENTANES:

ND = 1-fluoroneopentane C₃H₁,F

IR: 2960 (vs), 2890 (ms), 1480 (m,br), 1410 (w), 1400 (w), 1380 (sh),
1370 (m), 1360 (sh), 1290 (w,br), 1220 (w,br), 1190 (w), 1045 (s),
1025 (m), 1015 (s), 1005 (m), 905 (w)

MS: CI: 89 (1.1) C_5FH_{10} (M-H); 75 (2.8) C_4FH_8 (M-CH₃); 71 (100) C_5H_{11} (M-F); 69 (3.0) C_5H_9 ; 59 (1.0) C_3FH_4

EI: 75 (38.5) C_4FH_8 ; 57 (100) C_3FH_2 or C_4H_9 ; 55 (61.1) C_3F or C_4H_7 ; 47 (57.1) C_2FH_4 ; 41 (81.6) C_3H_5 ; 39 (47.3) C_3H_3 ; 33 (25.8) CFH_2 ; 29 (71.2) C_2H_5 ; 27 (37.1) C_2H_3 .

NL = 1,3-difluoroneopentane C₅H₁₀F₂

IR: 2970 (s), 2900 (m), 1480 (m), 1405 (w), 1370 (w); 1055, 1050, 1040, 1030 (vs); 995, 990 (mw), 910 (w)

MS: CI: 89 (38.3) $C_4F_2H_3$; 75 (18.1) C_3F_2H ; 69 (100) C_4FH_2 or C_5H_9 : 59 (45.6) C_3FH_4

EI: 75 (89.7) C_3F_2H ; 73 (10.4) C_4FH_6 ; 69 (17.7) C_4FH_2 or C_5H_9 ; 59 (16.0) C_3FH_4 ; 55 (76.1) C_4H_7 or C_3F ; 53 (12.2) C_4H_5 ; 51 (12.1) CF_2h or C_4H_3 ; 47 (100) C_2FH_4 ; 41 (23.5) C_3H_5 ; 39 (36.3) C_3H_3 ; 33 (48.8) CFH_2 ; 29 (58.1) C_2H_5 ; 27 (44) C_2H_3 .

NF' = 1.1-difluoroneopentane C₅H₁₀F₂

IR: 2970 (m), 2880 (w), 1490 (w,br), 1410 (w), 1370 (w),
1290 (w,br), 1110 (s), 1100 (ms), 1085 (ms), 1080 (s),
1030 (mw), 905 (w)

MS: CI: $89 (100) C_5H_{10}F (M-F)$; 87 (1.8) C_5H_8F ; 71 (4.2) C_5H_{11} ; 69 (11.5) C_4FH_2 or C_5H_9 ; 59 (5.1) C_3FH_4

EI: 65 (44.6) $C_2F_2H_3$ or C_5H_5 ; 57 (100) C_3FH_2 or C_4H_9 51 (30.5) CF_2H or C_4H_3 ; 47 (18.4) C_2FH_4 ; 41 (88.3) C_3H_5 ; 39 (35.1) C_3H_3 ; 29 (45.4) C_2H_5 ; 27 (22.2) C_2H_3

NO = Sym. trifluoroneopentane C.H.F.

IR: 2970 (m), 2900 (mw), 1470 (w,br), 1390 (w,br), 1290 (w,br), 1200 (w,br), 1050/1040 (vs), 980 (w), 935 (vw)

MS: CI: 117 (40.6) C_5F_3 ; 87 (100) C_4F_2H or C_5H_8F ; 67 (29.9) C_4F or C_5H_7 ; 59 (64.3) C_3FH_4

EI: 77 (11.6) $C_3F_2H_3$; 59 (20.7) C_3FH_4 ; 53 (20.4) C_4H_5 ; 51 (19.3) C_4H_3 ; 47 (100) C_2FH_4 ; 43 (12.1) C_2F ; 41 (15.1) C_3H_5 ; 39 (23.5) C_3H_3 ; 33 (47.8) CFH_2 ; 29 (19.4) C_2H_5 ; 27 (26.8) C_2H_3 .

Elemental Analysis: Calc. %C 47.62; %H 7.19; %F 45.19

C₅H₅F₃ Found: %C 47.68; %H 7.33; %F 45.16; %F

NK' = asym. trifluoroneopentane C.H.F.

IR: 2980 (ms); 2900 (w), 1480 (w), 1410 (w), 1370 (w), 1190 (w), 1120 (s), 1110 (ms), 1100 (sh), 1090 (s), 1040 (sh), 1030 (s), 990 (w), 905 (w)

MS: CI: $\underline{117 (100) C_5F_3}$; 87 (66.5) C_4F_2H ; 67 (17.5) C_4F EI: 93 (14.3) C_3F_3 ; 75 (100) C_3F_2H ; 65 (68.5) C_5H_5 ; 59 (14.5) C_3FH_4 ; 55 (61.8) C_3F ; 51 (30.3) CF_2H ; 47 (71.0) C_2FH_4 ; 43 (10.9) C_2F ; 41 (11.4) C_3H_5 ; 39 (20.1) C_3H_3

Elemental Analysis: Calc. %C 47.62; H 7.19; %F 45.19

C₅H₉F₃ Found: %C 47.79; %H 7.41; %F 45.00;

NN = 1.1.3.3-tetrafluoroneopentane C.H.F.

IR: 2980 (w,br), 1470 (w,br), 1390 (mw,br), 1240 (mw), 1215 (m),
1180 (m), 1145 (sh), 1130 (ms), 1100 (s), 1080 (sh), 980 (w),
660 (w)

MS: CI: 141_(100) C₅F₄H₅

EI: 69 (14.8) C_4FH_2 or C_5H_9 ; 65 (10.5) C_5H_5 ; 64 (14.0) C_5H_4 ; 59 (55.3) C_3FH_4 ; 57 (12.2) C_3FH_2 ; 51 (100) CF_2H 39 (15.2) C_3H_3

TABLE 7 (CONTINUED) (b)

NO = asym. tetrafluoroneopentane C₅H₆F₆

- MS: CI: 133 (14.8) $C_3F_5H_2$?; 125 (14.7) C_4F_4H ; 119 (18.9) $C_5F_3H_2$ 117 (100) C_5F_3 ; 105 (56.1) C_4F_3 ; 85 (46.0) C_5FH_6 ; 75 (52.6) C_3F_2H ; 73 (12.8) C_4FH_6
 - EI: 93 (26.5) C_3F_3 ; 77 (15.7) $C_3F_2H_3$; 73 (48.6) C_4FH_6 ; 71 (10.7) C_4FH_4 ; 59 (27.2) C_3FH_4 ; 53 (16.9) C_4H_5 ; 59 (27.2) C_3FH_4 ; 53 (16.9) C_4H_5 ; 51 (61.2) CF_2H ; 47 (100) C_2FH_4 ; 41 (23.4) C_3H_5 ; 39 (28.1) C_3H_3 ; 33 (35.8) CFH_2 ; 29 (10.7) C_2H_5 ; 27 (17.4) C_2H_3

Elemental Analysis: Calc. %C 41.67; %H 5.60; %F 52.73

C₅H₈F₄ Found: %C 39.57; %H 5.51; %F (54.92)

NT = sym.-pentafluoroneopentane

- IR: 2986 (s), 2923 (m), 1480 (m), 1388 (br,m), 1282 (m), 1205 (sh),
 1198 (ms), 1180 (ms), 1165 (sh), 1108 (ms), 1099 (sh), 1090 (s),
 1080 (sh), 1065 (sh), 1057 (m); 1044 (sh), 1037 (vs)
- MS: CI: 181 (6.9) C_4F_7 (1mp) 163 (4.7) $C_5F_5H_8$; 143 (4.0) $C_5F_4H_7$ 141 (5.6) $C_5F_4H_5$; 125 (16.6) C_4F_4H ; 123 (100.0) $C_5F_3H_6$; 105 (78.7) C_4F_3 ; 103 (19.0) $C_5F_2H_5$; 85 (15.5) SiF₃; 79 (12.9) $C_3F_2H_5$; 77 (54.8) $C_3F_2H_3$; 73 (15.1) C_4F_4 ; 65 (5.3) $C_2F_2H_3$; 59 (30.0) C_3F_4
 - EI: $163 (5.0) C_4F_6H(imp)$; $131 (5.9) C_3F_5$; $119 (6.9) C_2F_5$; $111 (29.5) C_4F_3H_6$; $110 (35.3) C_4F_3H_5$; $109 (9.6) C_4F_3H_4 95 (20.7) C_3F_3H_2$; $92 (14.2) C_4F_2H_6$; $91(100.0) C_4F_2H_5$; $89 (12.5) C_4F_2H_3$;

TABLE 7 (CONTINUED) (c)

85 (11.8) $C_3F_2H_9$; 77 (77.1) $C_4F_2H_5$; 71 (25.3) C_4FH_5 ; 69 (26.6) CF_3 ; 65 (44.1) $C_2F_2H_3$; 59 (55.4) C_3FH_4 ; 58 (28.7) C_3FH_3 ; 57 (14.3) C_3FH_2 ; 51 (47.1) CF_2H ; 44 (13.2) C_2FH ; 43 (46.6) C_2F 39 (11.2) C_3H_3 ; 33 (12.3) CFH_2 .

Elemental Analysis: Calc. %C 37.05; %H 4.35 %F 58.60 C₅H₇F₅ Found: %C 37.40; %H 4.67 %F 58.46

NR = hexafluoroneopentane C₅H₆F₆

IR: 2980 (mw), 2910 (w), 1480 (w), 1390 (m), 1290 (w,br), 1190 (s), 1110 (s,br), 1060 (sh), 1040 (sh), 970 (w), 910 (m), 670 (w)

MS: CI: $\underline{141 (100) C_5F_4H_5}$; 121 (11.4) $C_5F_3H_4$; 91 (25.0) $C_4F_2H_5$; 77 (49.6) $C_3F_2H_3$; 65 (31.9) C_5H_5 ; 59 (61.0) C_3FH_4

EI: 95 (45.3) $C_3F_3H_2$; 91 (10.1) $C_4F_2H_5$; 89 (12.2) $C_4F_2H_3$; 77 (80.6) $C_3F_2H_3$; 65 (10.0) C_5H_5 ; 59 (100) C_3FH_4 ; 57 (19.2) C_3FH_2 ; 51 (75.1) CF_2H ; 39 (12.4) C_3H_3 ; 33 (12.5) CFH_2

Elemental Analysis: Calc. %C 33.35; %H 3.36; %F 63.29

C₅H₆F₆ Found: %C 33.25; %H 3.44; %F 62.91

NP = heptafluoroneopentane C-H-F-

IR: 3000 (sh), 2975 (w), 2900 (sh), 1480 (w), 1390 (m), 1190 (vs,
with several shoulders), 1110 (s), 1070 (s), 1030 (sh), 945
(w), 790 (w), 600 (w)

MS: CI: 217 (11.6) $C_5F_8H_5$; 159 (4.0) $C_5F_5H_4$; 109 (100.0) $C_4F_3H_4$. EI: 270 (2.6) $C_5F_{11}H$; 219 (3.6) C_4F_9 ; 181 (1.7) C_4F_7 ; 145 (3.5) $C_4F_5H_2$; 131 (5.1) C_3F_5 ; 127 (14.9) $C_4F_4H_3$; 109 (37.4) $C_4F_3H_4$; 95 (25.9) $C_3F_3H_2$; 89 (10.0) ?; 77 (100.0) $C_3F_2H_3$; 69 (17.8) C_5 ; 59 (21.3) C_3F_4 ; 58 (34.5) C_3F_4 ; 57 (12.2) C_3F_4 ; 51 (42.0) C_5H_5 ; 43 (28.8) C_5F_5 .

TABLE 7 (CONTINUED) (d)

Elemental Analysis: Calc. %C 30.32; %H 2.54; %F 67.14

C₅H₅F₇ Found: %C 30.54; %H 2.69; %F 67.15

NK = sym. tetrahydro- \underline{F} -neopentane $C_5H_4F_8$

IR: 3000 (w), 1395 (m), 1365 (w), 1215 (ms), 1190 (vs), 1145/
1140 (m), 1120 (ms), 1100 (m), 1060 (m), 690 (m)

MS: CI: 107 (48.8) $C_4F_3H_2$; 127 (89.2) $C_4F_4H_3$; 87 (100) C_4F_2H EI: 75 (18.1) C_3F_2H ; 57 (19.5) C_3FH_2 ; 51 (100) CF_2H ; 47 (15.7) C_2FH_4

Elemental Analysis: Calc. %C 27.79; %H 1.87; %F 70.34

C₅H₄F₈ Found: %C 27.83; %H 1.89; %F 69.99

NI = asym. tetrahydryl-F-neopentane C₅H₄F₈

IR: 3000 (w), 1400 (w), 1380 (m), 1305 (m), 1260 (sh), 1240 (vs), 1170 (m), 1120 (s), 1110 (sh), 1060 (s), 1025 (mw), 680 (mw)

MS: CI: $\underline{145 \ (100) \ C_4F_5H_2}$; 125 (11.8) C_4F_4H ; 119 (12.1) $C_5F_3H_2$; 117 (11.1) C_5F_3 ;

EI: 75 (13.4) C_3F_2H ; 69 (17.0) CF_3 ; 51 (100) CF_2H 33 (16.6) CFH_2

Elemental Analysis: Calc. %C 27.79; %H 1.87; %F 70.34

C₅H₄F₈ Found: %C 27.90; %H 1.93; %F 70.54

NH = sym. trihydryl-F-neopentane C₅H₃F₉

IR: 3000 (w), 1380 (m), 1275 (s), 1240 (s), 1170 (m), 1100 (m), 1055 (m), 1010 (mw), 980 (w), 690 (mw), 660 (w)

MS: CI: 127 (100) C4F4H3

EI: 77 (3.6) $C_3F_2H_3$; 69 (12.1) CF_3 ; 57 (3.1) C_3FH_2 ; 51 (100) CF_2H ; 31 (4.7) CF

Elemental Analysis: Calc. %C 25.66; %H 1.29; %F 73.05

C₅H₃F₉ Found: %C 25.90; %H 1.56; %F 72.73

TABLE 7 (CONTINUED) (e)

NG = 2.2-(bistrifluoromethyl)-1.1.3-trifluoropropane

IR: 3013 (w), 2999 (sh), 2930 (vw), 1485 (vw), 1412 (sh), 1400 (m), 1375 (m), 1315 (s), 1300 (sh), 1280 (vs), 1258 (vs), 1202 (mw), 1178 (m), 1126 (m), 1106 (m), 1072 (ms), 1025 (ms), 980 (w), 876 (mw), 845 (vw), 818 (vw), 735 (w), 705 (vw), 678 (vw)

MS: CI: 215 (2.2) $C_5H_3F_8$; 203 (3.4) $C_4H_3F_8$; 193 (13.3) C_5F_7 ; 145 (36.7) $C_4F_5H_2$; 127 (10.9) $C_4F_4H_3$; 119 (5.4) C_2F_5 ; 107 (5.0) $C_4F_3H_2$; 101 (8.5) C_2F_4H ; 95 (10.9) $C_3F_3H_2$; 79 (100.0) $C_3F_2H_5$; 77 (24.5) $C_3F_2H_3$

EI: 182 (8.0) C_4F_7H ; 181 (6.6) C_4F_7 ; 164 (9.7) $C_4F_6H_2$; 163 (35.8) 95 (95.7) $C_3F_3H_2$; C_4F_6H ; $\frac{145}{100.0}$ $C_4F_5H_2$; 113 (33.8) C_3F_4H ; 96 (17.1) $C_3F_3H_3$; 77 (17.2) $C_3F_2H_3$; 75 (13.4) C_3F_2H ; 69 (37.3) CF_3 ; 51 (34.9) CF_2H

Elemental Analysis: Calc. %C 25.66; %H 1.29; %F 73.05

C₅H₃F₉ Found: %C 25.87; %H 1.33; %F 72.65

Intensity symbols used in IR-Listings are:

vs very strong, s strong, ms medium-strong, m medium, sh shoulder,

mw medium-weak, w weak, vw very weak, br broad.

TABLE 8

% PRODUCT DISTRIBUTIONS FROM SELECTED AEROSOL FLUORINATIONS OF NEOPENTANE
(ESTIMATED FROM PEAK AREAS OF GLC-TRACES)

	F/N-1	F/N-6	F/N-7	F/N-11	F/N-16	F/N-17	F/N-20	F/N-21
*	4.0	0.5	0.3	* =	unreact	ed neope	ntane	
NA						0.3	4.0	4.0
NB						0.6	9.2	9.0
NC						4.4	24.0	19.4
ND	21.8	7.6	3.2					
NE					0.7	11.2	32.6	18.6
NF '	4.3	2.5	1.6					
NG					4.1	5.1	3.3	5.0
NH					3.9	18.9	20.8	14.7
NI					15.7	17.4		10.3
NK '	10.7	10.1	8.7					
NK					12.4	18.7	6.2	10.2
NL	37.9	20.1	10.3					
NM				4.6	9.6	3.5		1.5
NN				1.6	1.5			
NO	6.5	17.4	23.9	14.7	7.4			
NF		2.8	3.8	14.3	6.4			
NP		0.9	1.3	6.1	18.1	15.2		6.5
NQ	12.8	16.2	14.0	2.2				
NR		4.1	7.6	24.7	14.9	3.5		0.7
NS	1.8	(3.6) 17.8	(5.1) 25.3					
NT		(14.2)	(20.2)	31.8	5.3	1.3		

Marin Wall

TABLE 9

IDENTITIES OF PRODUCTS FROM NEOPENTANE FLUORINATIONS

ef. No.	Structure	Name
NA	F-C(CF ₃) ₃	perfluoroisobutane
NB	C(CF ₃) ₄	perfluoroneopentane 14,32
NC	CF ₂ H-C(CF ₃) ₃	undecafluoroneopentane 32
		≡ 1-hydry1- <u>F</u> -neopentane
ND	CFH ₂ -C(CH ₃) ₃	1-fluoroneopentane
NE	$(CF_2H)_2C(CF_3)_3$	sym. decafluoroneopentane 32
		\equiv 1,3-dihydry1- \underline{F} -neopentane
NF 1	CF ₂ H-C(CH ₃) ₃	1,1-difluoroneopentane
NG	$CFH_2-C(CF_2H)(CF_3)_2$	asym. nonafluoroneopentane
		\equiv 1,1,3-trihydryl- \underline{F} -neopentane
NH	CF ₃ -C(CF ₂ H) ₃	sym. nonafluoroneopentane
NI	$CF_3-C(CFH_2)(CF_2H)_2$	asym. octafluoroneopentane
NK	C(CF ₂ H) ₄	sym. octafluoroneopentane
NK '	$CF_2H-C(CFH_2)(CH_3)_2$	asym. or 1,1,3-trifluoroneopentane
NL	$(CH_3)_2C(CFH_2)_2$	sym. or 1,3-difluoroneopentane
NN	$(CF_2H)_2C(CH_3)_2$	1,1,3,3-tetrafluoroneopentane
NO	CF ₂ H-C(CH ₃)(CFH ₂) ₂	asym. tetrafluoroneopentane
		<pre></pre>
NP	(CF ₂ H) ₃ C-CFH ₂	heptafluoroneopentane
		<pre>= 1,1,3-trifluoro-2,2-bis(difluoromethyl)propane</pre>
NQ	(CFH ₂) ₃ C-CH ₃	sym. trifluoroneopentane
		<pre> = 1-fluoro-2,2-bis(fluoromethyl(propane) </pre>
NR	$(CFH_2)_2C(CF_2H)_2$	hexafluoroneopentane
		<pre>= 1,1,3,3-tetrafluoro-2,2-bis(fluoromethyl)propane</pre>
NS	C(CFH ₂) ₄	sym. tetrafluoroneopentane
NT	CF ₂ H-C(CFH ₂) ₃	pentafluoroneopentane
		≡ 1,1,3-trifluoro-2,2-bis(fluoromethy1)propane
*	C(CH ₃) ₄	unreacted neopentane

TABLE 10

REACTION CONDITIONS FOR PHOTOCHEMICAL FLUORINATIONS OF NEOPENTANE
IN THE AEROSOL REACTOR DESIGNATED (X)

pof No	hydrocarbon flow	h.c. carrier	main carrier	1 1	_	in stag	-	7	F ₂ dil. He flow
Ref. No.	[mmoles/h]	[cc/min]	[cc/min] 1	2	. 3	4	Σ	[cc/min]
PF/N-1	2	43	400	0.8	0.3	0	0	1.1	4 x 5
PF/N-2	2	43	400	2.0	0	0	0	2.0	4 x 5
PF/N-4	2	43	400	5.0	5.0	0	0	10.0	4 x 5
PF/N-5	2	43	400	10.0	0	0	0	10.0	4 x 5
PF/N-6	4	100	1200	20.0	20.0	0	0	40.0	4 x 5
PF/N-7	1	101	400	20.0	20.0	60.0	100.0	200.0	4 x 5

	-	ratur modul		c]				ichiom n stag	•			reaction time
Ref. No.	reactor	#1	#2	coil	hc:F2	1	2	3	4	Σ	% F ₂	[sec]
PF/N-1	- 65	-30	0	RT	1:1.3	0.08	0.03	0	0	0.11	0.24	175
PF/N-2	- 65	-30	0	RT	1:2.4	0.20	0	0	0	0.20	0.43	175
PF/N-3	- 65	-30	0	RT	1:6.0	0.50	0	0	0	0.50	1.07	174
PF/N-4	- 65	-30	0	RT	1:12.0	0.50	0.50	0	0	1.00	2.11	172
PF/N-5	- 65	-30	0	RT	1:12.0	1.00	0	0	0	1.00	2.11	172
PF/N-6	- 65	-30	0	RT	1:24.0	1.00	1.00	0	0	2.00	2.94	60
PF/N-7	-65	-30	0	RT	1:48.0	4.0	4.0	12.0	20.0	40.0	27.74	113

TABLE 11

The second secon

REACTION CONDITIONS FOR PHOTOCHEMICAL FLUORINATIONS OF 1,4-DIOXANE (PF/D); CYCLOHEXANE (PF/C)
AND 2-2-DIMETHYL-1,3-DIOXOLANE (PF/DMD) IN THE AEROSOL REACTOR DESIGNATED (X)

	hydrocarbon	h.c.	main		FF 2	F ₂ flows [cc/min] in stage	/min]		F ₂ dil. He flow
Ref. No.	[mmoles/h]	[cc/min]	[cc/min]	1	2	3	4	Σ,	[cc/min]
F/D-1	1	63.5 ^a	400	20	20	09	100	200	4 x 5
PF/D-1	2	63 ^b	400	20	20	09	100	200	4 x 5
PF/C-1	2	29 ^a	400	20	20	09	100	200	4 x 5
PF/DMD-1	2	20 _C	400	20	20	09	100	200	4 x 5

*
Hydrocarbon reservoir temp: (a) $0^{\circ}C$ (b) $10^{\circ}C$ (c) $39^{\circ}C$

	temp	temperature [°C]	, [°c]				sto ;	stoichiometry	try			reaction
		modules	S		F.	-	,	11 Stage	7	٨	7 . % F.	[sec]
Ref. No. reactor	reactor	#1	# T# # 7	ł	CO11 DC:F2	1	7		1	7	2	
F/D-1	-65	-30	0 R	0 RT/45°C 1:480	1:480	9	9	18	30	09	29.3	134
PF/D-1	-65	-30	0	RT	1:240	က	3	6	15	30	29.3	119
PF/C-1	-65	-30	0	RT	1:240	2	2	9	10	20	30.8	125
PF/DMD-1	-65	-30	0	RT	1:240	2.4	2.4 2.4 7.2	7.2	12	24	31.2	127
		,										

*** Reactor designation (V) two coils no UV.

REFERENCES

- 1. R. D. Chambers, "Fluorine in Organic Chemistry," Wiley Interscience, New York, 1973, page 22.
- 2. J. H. Simons, U.S. Patent 2,5000,000 (1950).
- J. Burdon and J. C. Tatlow, Advan. Fluorine Chem., 1, 77 (1967).
- 4. J. H. Simons, Trans. Electrochem. Soc., 95, 47 (1949).
- 5. J. H. Simons, in <u>Fluorine Chemistry</u>, Academic, New York, 195, Vol. 1, p. 401.
- 6. R. D. Fowler, W. B. Burford, J. M. Hamilton, R. G. Sweet, C. E. Weber, J. S. Kasper and I. Litant in <u>Preparation</u>, <u>Properties and Technology of Fluorine and Organo-Fluorine Compounds</u>, C. Slesser and S. R. Schram, Eds., McGraw-Hill, N.Y., 1951, p. 349.
- 7. R. D. Bagnall, P. L. Coe and J. C. Tatlow, <u>J. Fluorine Chem.</u>, <u>3</u>, 329 (1974).
- 8. E. A. Tyczkowski and L. A. Bigelow, <u>J. Amer. Chem. Soc.</u>, <u>77</u>, 3007 (1955).
- 9. A. F. Maxwell, F. E. Detoro and L. A. Bigelow, <u>J. Amer. Chem. Soc.</u>, <u>82</u>, 5827 (1960).
- B. C. Bishop, J. B. Hynes and L. A. Bigelow, <u>J. Amer. Chem. Soc.</u>, <u>86</u>, 1827 (1964).
- 11. J. L. Margrave and R. J. Lagow in Chem. Eng. News, Jan 12, p. 40 (1970).
- 12. R. J. Lagow and J. L. Margrave, <u>Proc. Natl. Acad. Sic., 67</u>, 4, 8A (1970).
- 13. R. J. Lagow and J. L. Margrave, J. Polymer Science, 12, 177 (1974).
- N. J. Maraschin and R. J. Lagow, J. Amer. Chem. Sci., 94, 8601 (1972).
- 15. N. J. Maraschin and R. J. Lagow, <u>Inorg. Chem.</u>, <u>12</u>, 1459 (1973).
- 16. J. L. Adcock and R. J. Lagow, J. Org. Chem., 38, 3617 (1973).
- 17. J. L. Adcock and R. J. Lagow, J. Amer. Chem. Soc., 96, 7588 (1974).
- 18. J. L. Adcock, R. A. Beh and R. J. Lagow, J. Org. Chem., 40, 3271 (1975).
- 19. J. L. Adcock and R. J. Lagow, unpublished results.
- 20. J. L. Adcock, B. D. Catsikis, J. W. Thompson and R. J. Lagow, J. Fluorine Chemistry, 7, 197 (1976).
- 21. R. J. Lagow and J. L. Margrave, "Progress in Inorganic Chemistry," Vol. 26, p 161 (1979).

- 22. "Aerosol Science," Ch. 1, Academic Press, London and New York (1966), C. N. Davis, Ed.
- 23. R. D. Cadle, "Particle Size, Theory and Industrial Applications," Reinhold, New York (1965).
- 24. G. M. Hidy, "Aerosols and Atmospheric Chemistry" Reinhold Papers Contributed Kendall Award Symposium, American Chemical Society, Los Angeles, California, March 28-April 2, 1971, Academic Press, New York and London (1972). "The Kinetics of Growth of an Aerosol in a Flow Reactor, S. Shahriari, A. N. Sarmiento and F. C. Goodrich, p. 67.
- 25. A. G. Sutugin, Advances in Aerosol Physics, $\frac{4}{2}$, 36 (1971 translated from Russian 1973).
- 26. W. Espenscheid, E. Matijevic and M. Kerker, J. Phys. Chem., Ithaca, 68, 2831 (1964).
- 27. "Simultaneous Fluorination and Functionalization of Hydrocarbon Polymers," J. L. Adcock, and Shoji Inoue and R. J. Lagow, J. Amer. Chem. Soc., 100, 1948 (1978), (b) U.S. Patent 4,114, 374.
- 28. "Fluorine Sensitized Oxidation of Hydrocarbons," J. L. Adcock, Presented at the 28th Southeast Regional Meeting ACS, Abstracts 451 (1976) and at the 174th ACS-National Meeting, Chicago, Illinois, August 31, 1977, Abstract FLUO-22.
- 29. "Simultaneous Fluorination and Functionalization of Neopentane and 1,4-Dioxane, J. Fluorine Chemistry, 16, 297 (1980).
- 30. J. L. Adcock and E. B. Renk, "Low Temperature Fluorination of Aerosol and Condensed Phase Sol Suspensions of Hydrocarbons Utilizing Elemental Fluorine," Office of Naval Research, (a) Contract Technical Reports No. 1 and (b) No. 2.
- 31. J. Gelas and S. Michaud, Bull. Soc. Chim. Fr., 1972, 2445.
- 32. J. Burdon and I. W. Parsons, Tetrahedron, 27, 4553 (1971).
- 33. M. Rey-Lafon, C. Rouffi, M. Camiade and M. Forel, J. Chim. Phys., 67, 2030 (1970).
- 34. F. A. Bovey, E. W. Anderson, F. P. Hood and R. L. Kornegay, <u>J. Chem. Phys.</u>, <u>40</u>, 3099 (1964).
- 35. Jean Cantacuzene and Real Jantzen, Tetrahedron Letters, 37, 3281 (1970).
- 36. R. D. Bagnall, W. Bell and K. Pearson, <u>J. Fluorine Chem.</u>, <u>9</u>, 359 (1977).
- J. L. Adcock and E. B. Renk, "Synthesis and Reactions of Perfluoroneopentyllithium," J. Organic Chem., 44, 3431 (1979).

TECHNICAL REPORT DISTRIBUTION LIST, GEN

	<u>No</u> . Copies		No. Copia
Office of Naval Research		U.S. Army Research Office	
Attn: Code 472		Attn: CRD-AA-IP	
800 North Quincy Street		P.O. Box 1211	
Arlington, Virginia 22217	2	Research Triangle Park, N.C. 27709	1
ONR Branch Office		Naval Ocean Systems Center	
Attn: Dr. George Sandoz		Attn: Mr. Joe McCartney	
536 S. Clark Street		San Diego, California 92152	1
Chicago, Illinois 60605	1	Name I I'm annua Connum	
OVD Promob Office		Naval Weapons Center	
ONR Branch Office		Attn: Dr. A. B. Amster,	
Attn: Scientific Dept.		Chemistry Division	1
715 Broadway New York, New York 10003	1	China Lake, California 93555	1
New fork, New fork [0005		Naval Civil Engineering Laboratory	
ONR Branch Office		Artn: Dr. R. W. Drisko	
1030 East Green Street		Port Hueneme, California 93401	
Pasadena, California 91106	1	roll ideneme, callionila 93401	-
rasadena, daliloinia jiioo	+	Department of Physics & Chemistry	
ONR Branch Office		Naval Postgraduate School	
Attn: Dr. L. H. Peebles		Monterey, California 93940	
Building 114, Section D		noncetty y designate 70740	-
666 Summer Street		Dr. A. L. Slafkosky	
Boston, Massachusetts 02210	1	Scientific Advisor	
		Commandant of the Marine Corps	
Director, Naval Research Laboratory		(Code RD-1)	
Attn: Code 6100		Washington, D.C. 20380	1
Washington, D.C. 20390	1		
-		Office of Naval Research	
The Assistant Secretary		Attn: Dr. Richard S. Miller	
of the Navy (R,ESS)		800 N. Quincy Street	
Department of the Navy		Arlington, Virginia 22217	1
Room 4E736, Pentagon			
Washington, D.C. 20350	•	Naval Ship Research and Development Center	
Commander, Naval Air Systems Command		Attn: Dr. G. Bosmajian, Applied	
Attn: Code 310C (H. Rosenwasser)		Chemistry Division	
Department of the Navy		Annapolis, Maryland 21401	1
Washington, D.C. 20360	1		
		Naval Ocean Systems Center	
Defense Documentation Center		Attn: Dr. S. Yamamoto, Marine	
Building 5, Cameron Station		Sciences Division	
Alexandria, Virginia 22314	12	San Diego, California 91232	1
Dr. Fred Saalfeld		Mr. John Boyle	
Chemistry Division		Materials Branch	
Naval Research Laboratory		Naval Ship Engineering Center	
Washington, D.C. 20375	:	Philadelphia, Pennsylvania 19112	1

TECHNICAL REPORT DISTRIBUTION LIST, GEN

No. Copies

1

Dr. Rudolph J. Marcus Office of Naval Research Scientific Liaison Group American Embassy APO San Francisco 96503

Mr. James Kelley
DTNSRDC Code 2803
Annapolis, Maryland 21402

STATE OF THE PARTY.

TECHNICAL REPORT DISTRIBUTION LIST, 053

	No. Copies		No. Copies
Dr. R. N. Grimes University of Virginia Department of Chemistry Charlottesville, Virginia 22901	1	Dr. M. H. Chisholm Department of Chemistry Indiana University Bloomington, Indiana 47401	1
Dr. M. Tsutsui Texas A&M University Department of Chemistry College Station, Texas 77843	1	Dr. B. Foxman Brandeis University Department of Chemistry Waltham, Massachusetts 02154	1
Dr. M. F. Hawthorne University of California Department of Chemistry Los Angeles, California 90024	1	Dr. T. Marks Northwestern University Department of Chemistry	
Dr. D. 3. Brown University of Vermont Department of Chemistry Burlington, Vermont 05401	1	Evanston, Illinois 60201 Dr. G. Geoffrey Pennsylvania State University Department of Chemistry	1
Dr. W. B. Fox Naval Research Laboratory Chemistry Division Code 6130 Washington D. C. 20375	1	University Park, Pennsylvania 16802 Dr. J. Zuckerman University of Oklahoma Department of Chemistry	Ĭ,
Dr. J. Adcock University of Tennessee Department of Chemistry Knoxville, Tennessee 37916	1	Norman, Oklahoma 73019 Professor O. T. Beachley Department of Chemistry State University of New York	1
Dr. A. Cowley University of Texas Department of Chemistry Austin, Texas 78712	1	Buffalo, New York 14214 Professor P. S. Skell Department of Chemistry The Pennsylvania State University University Park, Pennsylvania 16802	1
Dr. W. Hatfield University of North Carolina Department of Chemistry Chapel Hill, North Carolina 27514	1	Professor K. M. Nicholas Department of Chemistry Boston College Chestnut Hill, Massachusetts 02167	1
Dr. D. Seyferth Massachusetts Institute of Technology Department of Chemistry Cambridge, Massachusetts 02139	1	Professor R. Neilson Department of Chemistry Texas Christian University Fort Worth, Texas 76129	1
Professor H. Abrahamson University of Oklahoma Department of Chemistry Norman, Oklahoma 73019	1	Professor M. Newcomb Texas A&M University Department of Chemistry College Station, Texas 77843	1

